



致力环保板材事业，造福人类环境

## 寿光华林木业有限公司 SHOUGUANG HUALIN WOOD CO.,LTD

诚信 / 务实 / 创新 / 发展 Integrity / Pragmatic / Innovation / Development



### 寿光华林木业有限公司 SHOUGUANG HUALIN WOOD CO.,LTD

地址：山东省寿光市文庙街与正阳路交叉口西200米  
电话：0536-5261799  
传真：0536-5261799  
网址：www.hualinindustry.com  
邮箱：hualinindustry@gmail.com

Add: The West of the intersection of Wenmiao Street and Zhengyang Road, Shouguang City, Shandong P.R., China.

Tel: 86-536-5261799

Fax: 86-536-5261799

Http: www.hualinindustry.com

E-mail: hualinindustry@gmail.com



华林木业立志为中国木业作出更大贡献  
Hualin Wood determined to make greater contributions to China

诚信 / 务实 / 创新 / 发展  
Integrity / Pragmatic / Innovation / Development

## 企业简介 Company profile

寿光华林木业有限公司位于山东省寿光市，毗邻江北最大的板材生产基地山东昌乐，临近潍坊港，距离青岛港2小时车程，交通便利，是一家集合各类胶合板、密度板、刨花板、定向刨花板、门板等生产兼经营于一体的大型企业。

经过十几年的发展，公司拥有专业、丰富木材生产经验，拥有一级资质，完善的采购、加工、质检、营销管理机构，有雄厚的资金、专业人才和技术资源。

公司产品主要分为人造板系列和家具系列，人造板系列有建筑模板，常用贴面胶合板、密度板、刨花板、定向刨花板、单板层积材、门板等。公司获得了CARB、ISO9000、ISO14001质量证书，公司经营的产品畅销国内外市场，远销至美国、德国、澳大利亚、中东、非洲等，在客户中享有极好的声誉。


公司秉承以质量求生存、以创新求发展、以信誉求市场的经营宗旨，以优良的品质、合理的价格以及良好的合作信誉，满足不同客户的不同需要。公司积极开发国内外市场，努力实现公司经营多元化、全球化和综合化。

Shouguang Hualin Wood Co.Ltd is located in shouguang city, Shandong P.R. of China, near Qingdao & Weifang Port, enjoying convenient transportation access. We has specialized in manufacturing and exporting wood products for more than 10 years. Our products mainly including top grade film faced plywood, MDF, OSB, LVL, Door Skin, veneered panels etc. Our products are widely used in office, household and construction fields. Depending on excellent quality and after-sales control service, we have gained good reputation from clients all over the world, especially, USA, Germany, Australia, the Middle East and Africa and more.

We maintain "customer first, quality first" as our business purpose, and depend on advanced technology and scientific management. We are ready to cooperate with clients from all over the world and create good business in the future together.



### 建筑模板 Film Faced Plywood



品名 (Name): Film Faced Plywood  
 规格 (Size): 1220mm \* 2440mm \* 4—30mm; 1250mm \* 2500mm \* 4—30mm;  
 1525mm \* 3500mm \* 4—30mm  
 芯板 (Core): Poplar, Hardwood and Combi  
 面皮 (Face & Back): Black film, Brown film, Dynea film  
 胶水 (Glue): WBP, Melamine, MR

- Products vantages:
1. If put boiling water for 48 hours, it is still glue-sticking and non-deformed
  2. Physical mood is better than iron moulds and can satisfy the requirements of constructing mould while the iron ones are easy to be deformed and can hardly recover its smoothness even after repairing
  3. If used abide by the illustrations strictly, it can be reused more than 50 times, thus reducing the cost greatly and avoiding the disadvantages from (rusty and erosive of iron mould)
  4. Solves the problems of leaking and rough surface during constructing process
  5. Particularly suitable for watering concrete project because it can make the concrete surface smooth and flat
  6. Realizing a higher economic profits



品名 (Name): Veneer Plywood  
 规格 (Size): 1220mm \* 2440mm \* 1.0—40mm; 1250mm \* 2500mm \* 2.5—40mm;  
 1525mm \* 3500mm \* 2.5—40mm  
 芯板 (Core): Poplar, Pine, Birch, Hardwood and Combi  
 面皮 (Face & Back): Okoume, Bintangor, Poplar, Pine, Birch, Maple, Hardwood, Ash, Oak, Keruing  
 胶水 (Glue): E2/E1/E0/WBP/Melamine  
 用途 (Usage): Furniture, Decoration, Packing, Construction



### MDF 密度板

品名 (Name): MDF  
 规格 (Size): 4'8ft, 6'8ft, 6'9ft, 6'12ft  
 厚度 (Thickness): 2mm—30mm  
 胶水 (Glue): E0, E1, E2  
 Material: Panel Board with Pine and Hard Wood Fiber as raw material.  
 密度 (Density): 700-850kg/cbm  
 颜色 (Color): Solid colors or wood grain  
 外观 (Surface): Plain, Melamine or UV coated

Medium Density Fiberboard Test Report		
Inspection Item	Inspection Result	Technical Requirement
Dimension	1220*2440*18mm	
Density(g/cm <sup>3</sup> )	780	690-800
Formaldehyde Emission (Grading/100g)	10	E2≤12
Moisture content (%)	6.00%	4-13
Internal Bonding(Mpa)	1	≥0.55
Bending Strength(Mpa)	38	≥20
Elasticity coefficient(Mpa)	3698	≥2200
Screw Holding Strength	Surface:1644	≥1000
Inside Density Tolerance(%)	Edge:1334	±800
Water absorption and Thickness swelling	-0.9+±0.0	±7.0
	8.7	≤10

3

4



### OSB 定向刨花板

Product Name		OSB (Orient Strand Boards)
Spec.	Size	1220mm*2440mm&1250*2500mm or as your request
	Thickness	9mm-40mm
	Glue	MR/WBP/Melamine
	Material:	Poplar, Hardwood, Birch etc.
	Moisture	10%—16%
Grade	Density	650-700kg/cbm
	OSB1	MR glue for packing
	OSB2	Mositureproof Melamine glue for construction, indoor, furniture.
Certificate	OSB3	Waterproof WBP glue for construction outdoor etc.
	Usage	well sheathing, roofing, subflooring, flooring, packing, exhibition booths, decorative uses, hoarding and making portable building.

- Features:
- 1) Tight construction and high strength
  - 2) Minimum twisting, delamination or warping
  - 3) No rotten or decay, strong against corrosion and fire
  - 4) Water proof, consistent when exposed in the natural or wet environment
  - 5) Low formaldehyde emission
  - 6) Good nailing strength, easy to be sawn, nailed, drilled, grooved, planed, filed or polished
  - 7) Good heat and sound resistant, easy to be coated



5

### 门板, Door Skin

Product: HDF molded door skin  
 Surface: Wood veneered; White primed; Melamine finished  
 Face colour: Cherry, natural Walnut, Natura (Sapelli), Oak, Teak, Dark Walnut;  
 With wood grain or without Red Wood, split Smooth melamine surface,  
 no need to painting when making doors.  
 Height: 1850mm-2150mm  
 Width: 630mm-1050mm  
 Thickness: 3.0mm, 3.2mm, or 4.5mm  
 Design: 1 panel, 2 panels, 3 panels, 4 panels, 5 panels, 6 panels

### 宝丽板 Polyester Plywood

Description: Polyester plywood  
 Base board: Plywood, MDF  
 Polyester paper: According to customers request  
 Glue: MR, WBP, E1, E2, E0  
 Size(mm): 1220\*2440, 1250\*2500, 1220\*2500  
 Thickness(mm): 1.8-30mm 1/8inch(2.7-3.6mm); 1/4inch(6.0-6.5mm); 1/2inch(12-12.7mm); 5/8inch(15-16mm); 3/4inch(18-19mm)  
 Moisture: 10-16%  
 Thickness tolerance: ≤6mm ±0.2mm to 0.3mm  
 Packing: Inside pallets is wrapped with 0.2mm plastic bag, steel strip for strength with plywood sheets covered around the pallets goods  
 Quantity: 20GP 3pallets(21M<sup>3</sup>); 40GP 16pallets(42M<sup>3</sup>)  
 Features: Matt or glossy, or tactile design  
 MOQ: 1'20' 18 container  
 Payment: T/T or LC at sight  
 Delivery time: Within 15days after receiving deposit or Original LC at sight  
 Main Market: Russia, South America, Southern Asian, Middle east, Africa, etc.

Product Name		Block Board
Conventional data	Size	1220x2440mm&1500x2500mm or as your demand
	Thickness (3—25mm)	3/8inch(9.5—10.2mm)   9mm-37.3sheets/cbm   1/2inch(12—12.7mm)
		12mm-28sheets/cbm   5/8inch(15—16mm)   15mm-22.4sheets/cbm
		3/4inch(18—19mm)   18mm-18.86sheets/cbm
		Poplar /r paulownia, salcata etc.
Thickness to lerrance	Core	E0, E1
	Glue	Okoume, Bintangor, Red hardwood, Thickness of faced paper=0.25mm
	Grade	First class
	Moisture	≤12%
Physical parameter	±0.5mm	Equal to and more than 12mm
	±0.3mm	Less than 12mm
Density	450—750kg/cbm	
Transverse strength	≥15MPa(thickness≤16mm)	
	≥12MPa(thickness>16mm)	
Glue line shear strength	>1.0MPa	



细木工 Block board

6